Hodoyoshi-1

The future of remote sensing opened up by microsatellite





Hodoyoshi-1 is a 60 Kg, cubic microsatellite 60 cm on each side with aimed at Earth observation. It is equipped with a reaction wheel, a star sensor, a MEMS-based gyroscope, a GPS receiver, and is capable of accurate three-axis attitude control. Additionally, it will demonstrate orbit control capabilities with a novel propulsion system based on hydrogen peroxide. From a 500 Km sun-synchronous orbit, the satellite will obtain images with a ground resolution of 6.7 m in multiple spectral bands with a swath width of 28 Km. The mission specifications of Hodoyoshi-1 are equivalent to those of a traditional larger satellite heavier than 150 Kg.

Since 2010, the University of Tokyo has been developing a world-leading R&D project whose title is loosely translated as "Establishment of a New Paradigm of Space Development and Utilization with Microsatellites through the Original Japanese Concept of Reasonably Reliable (Hodoyoshi) Systems Engineering." The project' s aim is to further higher Japan' s technological competence in microsatellites and consolidate the leading position of Japan in this field through the collaboration between industry and academia.

Axelspace developed Hodoyoshi-1 in cooperation with the Next-generation Space Systems Technology Research Association (NESTRA), as the first microsatellite in the project. The mission accomplishments of this satellite will signify an important step towards the realization of AxelGlobe, our future real-time Earth observation platform consisting of a number of low-cost microsatellites similar to Hodoyoshi-1.

stem	Images with a ground resolution of 6.7 m obtained from Hodoyoshi-1
ociation(NST	Rean be used in a wide range of applications including agriculture,

forestry, fishery, map-making, GIS (geographic information system) and disaster monitoring.

We conducted a business demonstration experiment of using microsatellite images with two companies (Asia Air Survey Co., Ltd. and Kokusai Kogyo Co., Ltd.) and one institution (Remote Sensing Technology Center of Japan). Through this experiment, we have demonstrated the serviceability of remote-sensing images by microsatellites, making it the first step in deploying businesses in the future.

Hodoyoshi-1 carries an optical system capable of obtaining images with the ground resolution of 6.7 m. It uses CCD sensors in the blue, green, red and near-infrared spectral bands respectively. Near-infrared data will enable us to study the growth and health state of plants, which is undetectable with the visible bands alone.

Corporate Outline



Axelspace Corporation Clip Nihonbashi Building, 3-3-3 Nihonbashi-Honcho, Chuo-ku, Tokyo 103-0023, Japan Mail : info@axelspace.com URL : www.axelspace.com

Next generation Space system Technology Research Association(NS Dimentions : 503 × 524 × 524mm (Excluding Protrusions) Mass : 60 Kg Generated Power : 50 W Jaunch Date : November 6, 2014 4:35:48 PM	versity of Tokyo,
Technology Research Association(NS Dimentions : 503 × 524 × 524mm (Excluding Protrusions) Mass : 60 Kg Generated Power : 50 W Jaunch Date : November 6, 2014 4:35:48 PM	ation Space system
Dimentions : 503 × 524 × 524mm (Excluding Protrusions) Mass : 60 Kg Generated Power : 50 W	Research Association(NST
Mass : 60 Kg Generated Power : 50 W	24 × 524mm ing Protrusions)
Generated Power :50 W)
aunch Date · November 6, 2014 4:35:48 PM	
(Japan Standard Time)	r 6, 2014 4:35:48 PM In Standard Time)
Launch Vehicle :Dnepr Rocket	ocket
Orbit : Sun-Synchronous 500 Km Altitude	lynchronous (m Altitude
Current State : End of Operation	Operation